

Description

Diameter: 5/32", grip range: 0.376" - 0.437", universal head, oversized diameter, monel sleeve, corrosion resistant stem, CR3553 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR3553-5-7](#)

SKU / Model:	CR3553507
Minimum Qty (MOQ):	100
NSN:	5320-01-042-5146
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



P/N CR3553-5-07 Specifications

Fastener Length:	0.549 Inches Minimum And 0.569 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.172 Inches Minimum And 0.176 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.302 Inches Minimum And 0.322 Inches Maximum
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
Grip Length:	0.376 Inches Minimum And 0.437 Inches Maximum
Special Features:	Lubrication On Stem Only
Material:	Nickel Alloy 400 Body Or Nickel Alloy R-405 Body
Material:	Steel Comp 632 Stem
Material Document And Classification:	Ams 5657 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Body

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3553-5-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.