

**Description**

diameter: 5/32", grip range: 0.501" - 0.562", universal head, oversized diameter, monel sleeve, corrosion resistant stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[CR3553-5-9](#)

SKU / Model:	CR3553509
Minimum Qty (MOQ):	100
NSN:	5320-01-041-6452
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



\* See page 2 for technical characteristics

## P/N CR3553-5-09 Specifications

<b>Fastener Length:</b>	0.674 Inches Minimum And 0.694 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.067 Inches Minimum And 0.077 Inches Maximum
<b>Shank Diameter:</b>	0.174 Inches Minimum And 0.176 Inches Maximum
<b>Head Major Diameter:</b>	0.302 Inches Minimum And 0.322 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Lubrication:</b>	Dry Film
<b>Grip Length:</b>	0.501 Inches Minimum And 0.562 Inches Maximum
<b>Special Features:</b>	Lubrication On Stem Only
<b>Material:</b>	Nickel Alloy 400 Sleeve Or Nickel Alloy R-405 Sleeve
<b>Material:</b>	Steel Stem
<b>Material Document And Classification:</b>	Ams 5657 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec Single Material Response Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3553-5-09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.