

Description

Fastener Length: 5/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR3553-5-08](#)

| | |
|-------------------------|--|
| SKU / Model: | CR355358 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-042-8249 |
| Schedule B: | 7508.90.5000 |
| ECCN: | EAR99 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |



* See page 2 for technical characteristics

P/N CR3553-5-8 Specifications

| | |
|--|--|
| Fastener Length: | 0.611 Inches Minimum And 0.631 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.067 Inches Minimum And 0.077 Inches Maximum |
| Shank Diameter: | 0.172 Inches Minimum And 0.176 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.302 Inches Minimum And 0.322 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Lubrication: | Dry Film |
| Grip Length: | 0.438 Inches Minimum And 0.500 Inches Maximum |
| Special Features: | Lubrication On Stem Only |
| Material: | Nickel Alloy 400 Sleeve Or Nickel Alloy R-405 Sleeve |
| Material: | Steel Stem |
| Material Document And Classification: | Ams 5657 Assn Std Single Material Response Stem |
| Material Document And Classification: | Qq-n-281 Fed Spec Single Material Response Sleeve |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3553-5-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.