

Description

diameter: 3/16", grip range: 0.126" - 0.187", universal head, oversized diameter, monel sleeve, 15-7 ph corrosion resistant stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR3553-6-3](#)

SKU / Model:	CR3553603
Minimum Qty (MOQ):	100
NSN:	5320-01-288-7639
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N CR3553-6-03 Specifications

Fastener Length:	0.298 Inches Minimum And 0.328 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.200 Inches Minimum And 0.204 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.365 Inches Minimum And 0.385 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Material:	Steel Comp 632 Stem
Material Document And Classification:	Ams 5657 Assn Std Single Material Response Stem
Specification/standard Data:	81349-mil-r-7885/8 Government Specification
Nondefinitive Spec/std Data:	1 Type And B Style And 1 Class

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3553-6-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.