

Description

diameter: 3/16", grip range: 0.313" - 0.375", universal head, oversized diameter, monel sleeve, 15-7 ph corrosion resistant stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR3553-6-6](#)

SKU / Model:	CR3553606
Minimum Qty (MOQ):	100
NSN:	5320-01-041-6458
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



P/N CR3553-6-06 Specifications

Fastener Length:	0.505 Inches Minimum And 0.525 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.201 Inches Minimum And 0.205 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.365 Inches Minimum And 0.385 Inches Maximum
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
Grip Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Special Features:	Lubrication On Stem Only
Material:	Nickel Alloy 400 Sleeve Or Nickel Alloy R-405 Sleeve
Material:	Steel Stem
Material Document And Classification:	Ams 5657 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3553-6-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.