

Description

Blind Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|--|
| SKU / Model: | CR355362 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-296-6387 |
| ECCN: | EAR99 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |



NO IMAGE
AVAILABLE

P/N CR3553-6-2 Specifications

| | |
|--|---|
| Fastener Length: | 0.235 Inches Minimum And 0.265 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.080 Inches Minimum And 0.090 Inches Maximum |
| Shank Diameter: | 0.200 Inches Minimum And 0.204 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.365 Inches Minimum And 0.385 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.063 Inches Minimum And 0.125 Inches Maximum |
| Material: | Steel Comp 632 Stem |
| Material Document And Classification: | Ams 5657 Assn Std Single Material Response Stem |
| Specification/standard Data: | 81349-mil-r-7885/8 Government Specification |
| Nondefinitive Spec/std Data: | 1 Type And B Style And 1 Class |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3553-6-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.