

P/N CR3553-6-7

Description

Fastener Length: 5/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: CR355367

Minimum Qty (MOQ): 100

NSN: 5320-01-042-5149

ECCN: EAR99

National Motor Freight: 139820, Nickel Bolts / Nails / Nuts / Rivets Etc



^{*} See page 2 for technical characteristics

P/N CR3553-6-7 Specifications

Fastener Length:	0.568 Inches Minimum And 0.588 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.201 Inches Minimum And 0.205 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.365 Inches Minimum And 0.385 Inches Maximum
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
Grip Length:	0.376 Inches Minimum And 0.437 Inches Maximum
Special Features:	Lubrication On Stem Only
Material:	Nickel Alloy 400 Body Or Nickel Alloy R-405 Body
Material:	Steel Comp 632 Stem
Material Document And Classification:	Ams 5657 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Body

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/CR3553-6-7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.