

## Description

Fastener Length: 5/8

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	CR355368
Minimum Qty (MOQ):	100
NSN:	5320-01-042-5148
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



## P/N CR3553-6-8 Specifications

<b>Fastener Length:</b>	0.630 Inches Minimum And 0.650 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.080 Inches Minimum And 0.090 Inches Maximum
<b>Shank Diameter:</b>	0.201 Inches Minimum And 0.205 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.365 Inches Minimum And 0.385 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Lubrication:</b>	Dry Film
<b>Grip Length:</b>	0.438 Inches Minimum And 0.500 Inches Maximum
<b>Special Features:</b>	Lubrication On Stem Only
<b>Material:</b>	Nickel Alloy 400 Body Or Nickel Alloy R-405 Body
<b>Material:</b>	Steel Comp 632 Stem
<b>Material Document And Classification:</b>	Ams 5657 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec All Material Responses Body

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3553-6-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.