

Description

diameter: 1/8", grip range: 0.063" - 0.125", unisink head, oversized diameter, monel sleeve, corrosion resistant stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR3555-4-2](#)

SKU / Model:	CR3555402
Minimum Qty (MOQ):	100
NSN:	5320-01-224-8267
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



* See page 2 for technical characteristics

P/N CR3555-4-02 Specifications

Head Style:	Shovel
Head Height:	0.022 Inches Minimum And 0.032 Inches Maximum
Shank Diameter:	0.139 Inches Minimum And 0.143 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.210 Inches Minimum And 0.230 Inches Maximum
Countersink Height:	0.011 Inches Nominal
Expansion Device:	Plain Stem-type T
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Special Features:	Head Countersunk 100 Deg
Material:	Nickel Alloy R-405 Or Nickel Alloy 400 Sleeve
Material:	Steel Comp 632 Stem
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Sleeve
Material Document And Classification:	Ams 5657 Assn Std Single Material Response Stem
Specification/standard Data:	80205-nas9312 Professional/Industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3555-4-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.