

**Description**

diameter: 1/8", grip range: 0.126" - 0.187", unisink head, oversized diameter, monel sleeve, corrosion resistant stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[CR3555-4-3](#)

SKU / Model:	CR3555403
Minimum Qty (MOQ):	100
NSN:	5320-01-224-8268
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N CR3555-4-03 Specifications

<b>Head Style:</b>	Shovel
<b>Head Height:</b>	0.022 Inches Minimum And 0.032 Inches Maximum
<b>Shank Diameter:</b>	0.139 Inches Minimum And 0.143 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.210 Inches Minimum And 0.230 Inches Maximum
<b>Countersink Height:</b>	0.011 Inches Nominal
<b>Expansion Device:</b>	Plain Stem-type T
<b>Grip Length:</b>	0.126 Inches Minimum And 0.187 Inches Maximum
<b>Special Features:</b>	Head Countersunk 100 Deg
<b>Material:</b>	Nickel Alloy R-405 Or Nickel Alloy 400 Sleeve
<b>Material:</b>	Steel Comp 632 Stem
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec All Material Responses Sleeve
<b>Material Document And Classification:</b>	Ams 5657 Assn Std Single Material Response Stem
<b>Specification/standard Data:</b>	80205-nas9312 Professional/Industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3555-4-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.