

Description

Blind Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | CR355545 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-226-4972 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR3555-4-5 Specifications

| | |
|--|--|
| Head Style: | Shovel |
| Head Height: | 0.022 Inches Minimum And 0.032 Inches Maximum |
| Shank Diameter: | 0.139 Inches Minimum And 0.143 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.210 Inches Minimum And 0.230 Inches Maximum |
| Countersink Height: | 0.011 Inches Nominal |
| Expansion Device: | Plain Stem-type T |
| Grip Length: | 0.251 Inches Minimum And 0.312 Inches Maximum |
| Special Features: | Head Countersunk 100 Deg |
| Material: | Nickel Alloy R-405 Or Nickel Alloy 400 Sleeve |
| Material: | Steel Comp 632 Stem |
| Material Document And Classification: | Qq-n-281 Fed Spec All Material Responses Sleeve |
| Material Document And Classification: | Ams 5657 Assn Std Single Material Response Stem |
| Specification/standard Data: | 80205-nas9312 Professional/Industrial Association Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3555-4-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.