

**Description**

Fastener Length: 1/4

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	CR355553
Minimum Qty (MOQ):	100
NSN:	5320-01-226-4973
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N CR3555-5-3 Specifications

<b>Fastener Length:</b>	0.279 Inches Minimum And 0.309 Inches Maximum
<b>Head Style:</b>	Shovel
<b>Head Height:</b>	0.030 Inches Minimum And 0.040 Inches Maximum
<b>Shank Diameter:</b>	0.172 Inches Minimum And 0.176 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.276 Inches Minimum And 0.296 Inches Maximum
<b>Countersink Height:</b>	0.015 Inches Nominal
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.126 Inches Minimum And 0.187 Inches Maximum
<b>Special Features:</b>	Head Countersunk 100 Deg
<b>Material:</b>	Nickel Alloy R-405 Or Nickel Alloy 400 Sleeve
<b>Material:</b>	Steel Comp 632 Stem
<b>Material Document And Classification:</b>	Ams 5657 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec All Material Responses Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3555-5-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.