

Description

Blind Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	CR355563
Minimum Qty (MOQ):	100
NSN:	5320-01-226-4974
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR3555-6-3 Specifications

Head Style:	Shovel
Head Height:	0.040 Inches Minimum And 0.050 Inches Maximum
Shank Diameter:	0.200 Inches Minimum And 0.204 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.343 Inches Minimum And 0.363 Inches Maximum
Countersink Height:	0.023 Inches Nominal
Expansion Device:	Plain Stem-type T
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Special Features:	Head Countersunk 100 Deg
Material:	Nickel Alloy R-405 Or Nickel Alloy 400 Sleeve
Material:	Steel Comp 632 Stem
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Sleeve
Material Document And Classification:	Ams 5657 Assn Std Single Material Response Stem
Specification/standard Data:	80205-nas9312 Professional/Industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3555-6-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.