

Description

Blind Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|--|
| SKU / Model: | CR355563 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-226-4974 |
| Schedule B: | 7508.90.5000 |
| ECCN: | EAR99 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR3555-6-3 Specifications

| | |
|--|--|
| Head Style: | Shovel |
| Head Height: | 0.040 Inches Minimum And 0.050 Inches Maximum |
| Shank Diameter: | 0.200 Inches Minimum And 0.204 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.343 Inches Minimum And 0.363 Inches Maximum |
| Countersink Height: | 0.023 Inches Nominal |
| Expansion Device: | Plain Stem-type T |
| Grip Length: | 0.126 Inches Minimum And 0.187 Inches Maximum |
| Special Features: | Head Countersunk 100 Deg |
| Material: | Nickel Alloy R-405 Or Nickel Alloy 400 Sleeve |
| Material: | Steel Comp 632 Stem |
| Material Document And Classification: | Qq-n-281 Fed Spec All Material Responses Sleeve |
| Material Document And Classification: | Ams 5657 Assn Std Single Material Response Stem |
| Specification/standard Data: | 80205-nas9312 Professional/Industrial Association Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3555-6-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.