

Description

Fastener Length: 3/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	CR462351
Minimum Qty (MOQ):	100
NSN:	5320-01-025-1811
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



NO IMAGE
AVAILABLE

P/N CR4623-5-1 Specifications

Fastener Length:	0.201 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.292 Inches Minimum And 0.324 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.031 Inches Minimum And 0.062 Inches Maximum
Material:	Nickel Alloy 400 Locking Ring Or Nickel Alloy R-405 Locking Ring
Material Document And Classification:	Qq-n-281 CI A Fed Spec 1st Material Response Locking Ring Or Qq-n-281 CI B Fed Spec 2nd Material Response Locking Ring
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve
Surface Treatment Document And Classification:	Qq-p-416 Type 2,class 2 Fed Spec Single Treatment Response Sleeve
Specification/standard Data:	80205-nas1398 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR4623-5-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.