

Description

Fastener Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	CR462354
Minimum Qty (MOQ):	100
NSN:	5320-00-321-2521
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR4623-5-4 Specifications

Fastener Length:	0.388 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Stem
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Sleeve Or Ams 5731 Assn Std Single Material Response Sleeve Or Ams 5737 Assn Std Single Material Response Sleeve
Specification/standard Data:	80205-nas1398 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR4623-5-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.