

**Description**

Fastener Length: 1-5/8

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | CR4623611                                   |
| Minimum Qty (MOQ):      | 100   |
| NSN:                    | 5320-01-411-7166                            |
| Schedule B:             | 7318.23.0000                                |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N CR4623-6-11 Specifications

|   |  |
|---|--|
| <b>Fastener Length:</b>                               | 1.680 Inches Maximum   |
| <b>Head Style:</b>                                    | Universal  |
| <b>Head Height:</b>                                   | 0.080 Inches Minimum And 0.090 Inches Maximum  |
| <b>Shank Diameter:</b>                                | 0.186 Inches Minimum And 0.190 Inches Maximum  |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem   |
| <b>Head Major Diameter:</b>                           | 0.356 Inches Minimum And 0.394 Inches Maximum  |
| <b>Expansion Device:</b>                              | Serrated Stem-type W   |
| <b>Lubrication:</b>                                   | Dry Film Or Paraffin Wax Or Carbo Wax Or Cetyl Alcohol   |
| <b>Grip Length:</b>                                   | 0.626 Inches Minimum And 0.687 Inches Maximum  |
| <b>Special Features:</b>                              | Mech. Lock Ring.   |
| <b>Material:</b>                                      | Iron Alloy 660 Sleeve  |
| <b>Material:</b>                                      | Iron Alloy 660 Stem  |
| <b>Material:</b>                                      | Nickel Alloy 400 Locking Ring Or Nickel Alloy R-405 Locking Ring   |
| <b>Material Document And Classification:</b>          | Ams5731 Assn Std Single Material Response Stem   |
| <b>Material Document And Classification:</b>          | Ams5731 Assn Std Single Material Response Sleeve Or Ams5732 Assn Std Single Material Response Sleeve Or Ams5737 Assn Std Single Material Response Sleeve |
| <b>Material Document And Classification:</b>          | Qq-n-281 Fed Spec Single Material Response Locking Ring  |
| <b>Surface Treatment:</b>                             | Passivate Sleeve   |
| <b>Surface Treatment:</b>                             | Passivate Stem   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Sleeve  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Stem  |
| <b>Specification/standard Data:</b>                   | 1w025-03a062 Manufacturers Standard  |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR4623-6-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.