

**Description**

Fastener Length: 3/8", CR4623 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	CR462364
Minimum Qty (MOQ):	100
NSN:	5320-01-338-2859
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N CR4623-6-4 Specifications

<b>Fastener Length:</b>	0.365 Inches Minimum And 0.385 Inches Maximum
<b>Head Style:</b>	Undercut Pan No. 2
<b>Head Height:</b>	0.080 Inches Minimum And 0.090 Inches Maximum
<b>Shank Diameter:</b>	0.186 Inches Minimum And 0.190 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.365 Inches Minimum And 0.385 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.188 Inches Minimum And 0.250 Inches Maximum
<b>Material:</b>	Nickel Alloy Locking Ringiron Alloy 660 Sleeveiron Alloy 660 Stem
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec Single Material Response Locking Ringams 5731 Assn Std Single Material Response Sleeveams 5731 Assn Std Single Material Response Stem
<b>Surface Treatment:</b>	Passivate Locking Ringpassivate Sleevepassivate Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Locking Ringqq-p-35 Fed Spec Single Treatment Response Sleeveqq-p-35 Fed Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR4623-6-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.