

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CR911642
Minimum Qty (MOQ):	40 EA
NSN:	5320-00-957-1431
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N CR9116-4-2 Specifications

Fastener Length:	0.252 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.225 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Shear Strength:	125 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Aluminum Alloy 2117 Sleeve
Material:	Steel Comp 1006 Stem Or Steel Comp 1008 Stem Or Steel Comp 1010 Stem Or Steel Comp 1012 Stem Or Steel Comp 1015 Stem Or Steel Comp 1016 Stem Or Steel Comp 1018 Stem Or Steel Comp 1019 Stem Or Steel Comp 1021 Stem Or Steel Comp 1022 Stem Or Steel Comp 1026 Stem Or Steel Comp 1030 Stem Or Steel Comp 1035 Stem Or Steel Comp 1038 Stem Or Steel Comp 1524 Stem Or Steel Comp 1541 Stem
Material Document And Classification:	Astm A545 Assn Std All Material Responses Stem
Material Document And Classification:	Mil-w-7986 Mil Spec Single Material Response Sleeve
Surface Treatment:	Anodize Sleeve Or Chromate Sleeve
Surface Treatment Document And Classification:	Mil-a-8625 Ty 1 Cl 1 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Cl 1a Mil Spec 2nd Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR9116-4-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.