

Description

diameter: 1/8", grip range: 0.126" - 0.187", flush head, self plugging, 2117 aluminum sleeve, 2017 aluminum stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR9162-4-3](#)

SKU / Model:	CR9162403
Minimum Qty (MOQ):	100
NSN:	5320-00-582-3300
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N CR9162-4-03 Specifications

Fastener Length:	0.295 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Self-plugging
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Special Features:	W/special Pulling Head
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Mil-w-7986,h15 Mil Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Nondefinitive Spec/std Data:	2 Type And 2 Class

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR9162-4-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.