

**Description**

diameter: 1/8", grip range: 0.126" - 0.187", flush head, self plugging, 2117 aluminum sleeve, 2017 aluminum stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[CR9162-4-3](#)

SKU / Model:	CR9162403
Minimum Qty (MOQ):	100
NSN:	5320-00-582-3300
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

## P/N CR9162-4-03 Specifications

<b>Fastener Length:</b>	0.295 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.124 Inches Minimum And 0.128 Inches Maximum
<b>Shank Style:</b>	Self-plugging
<b>Head Major Diameter:</b>	0.221 Inches Minimum And 0.229 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.126 Inches Minimum And 0.187 Inches Maximum
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Special Features:</b>	W/special Pulling Head
<b>Material:</b>	Aluminum Alloy 2117 Overall
<b>Material Document And Classification:</b>	Mil-w-7986,h15 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Nondefinitive Spec/std Data:</b>	2 Type And 2 Class

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR9162-4-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.