

**Description**

diameter: 1/8", grip range: 0.251" - 0.312", 100°, flush head - self plugging - 2117 aluminum sleeve - 2017 aluminum stem"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	CR9162405
Minimum Qty (MOQ):	100
NSN:	5320-00-582-3275
National Motor Freight:	013630, Alum Rivets

NO IMAGE  
AVAILABLE

## P/N CR9162-4-05 Specifications

<b>Fastener Length:</b>	0.420 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.124 Inches Minimum And 0.128 Inches Maximum
<b>Shank Style:</b>	Self-plugging
<b>Head Major Diameter:</b>	0.221 Inches Minimum And 0.229 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.251 Inches Minimum And 0.312 Inches Maximum
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Special Features:</b>	W/special Pulling Head
<b>Material:</b>	Aluminum Alloy 2117 Body
<b>Material:</b>	Aluminum Alloy 2017 Stem
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Body
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Stem
<b>Surface Treatment:</b>	Anodize Overall Or Oxide Film Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR9162-4-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.