

Description

Fastener Length: 5/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | CR916248 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-00-835-5368 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N CR9162-4-8 Specifications

| | |
|---|--|
| Fastener Length: | 0.607 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.124 Inches Minimum And 0.128 Inches Maximum |
| Shank Style: | Self-plugging |
| Head Major Diameter: | 0.221 Inches Minimum And 0.229 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.438 Inches Minimum And 0.500 Inches Maximum |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Aluminum Alloy 2117 Sleeve |
| Material: | Aluminum Alloy 2017 Stem |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Sleeve |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Stem |
| Surface Treatment: | Chromate Stem |
| Surface Treatment: | Anodize Sleeve |
| Surface Treatment Document And Classification: | Mil-a-8625 Fed Spec 3rd Treatment Response Sleeve |
| Surface Treatment Document And Classification: | Mil-c-5541 Fed Spec 3rd Treatment Response Stem |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR9162-4-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.