

Description

Diameter: 5/32in., grip range: 0.080in. - 0.125in., flush head, self plugging, 2117 aluminum sleeve, 2017 aluminum stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR9162-5-2](#)

SKU / Model:	CR9162502
Minimum Qty (MOQ):	100
NSN:	5320-01-021-3457
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N CR9162-5-02 Specifications

<b>Fastener Length:</b>	0.245 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.156 Inches Nominal
<b>Shank Style:</b>	Self-plugging
<b>Head Major Diameter:</b>	0.286 Inches Nominal
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.063 Inches Minimum And 0.125 Inches Maximum
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Aluminum Alloy 2117 Overall Or Aluminum Alloy 2017 Overall
<b>Material Document And Classification:</b>	Aluminum Assn Of America Mfr Ref All Material Responses Overall

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR9162-5-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.