

Description

Diameter: 5/32in., grip range: 0.080in. - 0.125in., flush head, self plugging, 2117 aluminum sleeve, 2017 aluminum stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[CR9162-5-2](#)

| | |
|--------------------|------------------|
| SKU / Model: | CR9162502 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-021-3457 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N CR9162-5-02 Specifications

| | |
|--|--|
| Fastener Length: | 0.245 Inches Nominal |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.156 Inches Nominal |
| Shank Style: | Self-plugging |
| Head Major Diameter: | 0.286 Inches Nominal |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.063 Inches Minimum And 0.125 Inches Maximum |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Aluminum Alloy 2117 Overall Or Aluminum Alloy 2017 Overall |
| Material Document And Classification: | Aluminum Assn Of America Mfr Ref All Material Responses Overall |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR9162-5-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.