

Description

Diameter: 5/32in., grip range: 0.080in. - 0.125in., flush head, self plugging, 2117 aluminum sleeve, 2017 aluminum stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[CR9162-5-2](#)

SKU / Model:	CR9162502
Minimum Qty (MOQ):	100
NSN:	5320-01-021-3457
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N CR9162-5-02 Specifications

Fastener Length:	0.245 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.156 Inches Nominal
Shank Style:	Self-plugging
Head Major Diameter:	0.286 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 2117 Overall Or Aluminum Alloy 2017 Overall
Material Document And Classification:	Aluminum Assn Of America Mfr Ref All Material Responses Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR9162-5-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.