

Description

Diameter: 1/8", grip range: 0.025" - 0.062", universal head, self plugging, aluminum sleeve, aluminum stem, serrated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR9163-4-1](#)

SKU / Model:	CR9163401
Minimum Qty (MOQ):	100
NSN:	5320-00-582-3288
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N CR9163-4-01 Specifications

Fastener Length:	0.170 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Self-plugging
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	W/s:helicopter, Advance Attack, Ah-1w; Helicopter, Hh-53h Pave Low; Helicopter, Carrier Based Asw, Sh-60f; Helicopter, Search And Rescue, Hh-60h; Helicopter, Uscg Search And Rescue, Hh-60j; Helicopter, Mh-53e; U-2 Airframe; Air Conditioner, 60hz 9000btu; Defense Meteorological Satellite Program (dmsp); Air Conditioner, 30hz 1800btu
Grip Length:	0.062 Inches Maximum
Special Features:	W/special Pulling Head
Material:	Aluminum Alloy 2117 Body
Material:	Aluminum Alloy 2017 Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Body
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Stem
Surface Treatment:	Anodize Overall Or Oxide Film Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR9163-4-01> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.