

Description

diameter: 1/8", grip range: 0.251" - 0.312", universal head, self plugging, 2117 aluminum sleeve, 2017 aluminum stem, serrated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[CR9163-4-5](#)

SKU / Model:	CR9163405
Minimum Qty (MOQ):	100
NSN:	5320-01-019-1532
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N CR9163-4-05 Specifications

Fastener Length:	0.410 Inches Nominal
Head Style:	Universal
Head Height:	0.054 Inches Nominal
Shank Diameter:	0.125 Inches Nominal
Shank Style:	Self-plugging
Head Major Diameter:	0.250 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.251 Inches Minimum And 0.312 Inches Maximum
Material:	Aluminum Alloy 2117 Overall Or Aluminum Alloy 2017 Overall
Material Document And Classification:	Aluminum Assn Of America Mfr Ref All Material Responses Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	11815 Mfr Ref Single Treatment Response Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR9163-4-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.