

Description

diameter: 1/8", grip range: 0.251" - 0.312", universal head, self plugging, 2117 aluminum sleeve, 2017 aluminum stem, serrated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[CR9163-4-5](#)

| | |
|--------------------|------------------|
| SKU / Model: | CR9163405 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-019-1532 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N CR9163-4-05 Specifications

| | |
|---|---|
| Fastener Length: | 0.410 Inches Nominal |
| Head Style: | Universal |
| Head Height: | 0.054 Inches Nominal |
| Shank Diameter: | 0.125 Inches Nominal |
| Shank Style: | Self-plugging |
| Head Major Diameter: | 0.250 Inches Nominal |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.251 Inches Minimum And 0.312 Inches Maximum |
| Material: | Aluminum Alloy 2117 Overall Or Aluminum Alloy 2017 Overall |
| Material Document And Classification: | Aluminum Assn Of America Mfr Ref All Material Responses Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | 11815 Mfr Ref Single Treatment Response Overall |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR9163-4-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.