

## Description

diameter: 1/8", grip range: 0.313" - 0.375", universal head, self plugging, aluminum sleeve, aluminum stem, serrated

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

### Alternate Part Numbers

[CR9163-4-6](#)

SKU / Model:	CR9163406
Minimum Qty (MOQ):	100
NSN:	5320-00-582-3495
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

## P/N CR9163-4-06 Specifications

<b>Fastener Length:</b>	0.482 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.054 Inches Minimum And 0.064 Inches Maximum
<b>Shank Diameter:</b>	0.124 Inches Minimum And 0.128 Inches Maximum
<b>Shank Style:</b>	Self-plugging
<b>Head Major Diameter:</b>	0.238 Inches Minimum And 0.262 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.313 Inches Minimum And 0.375 Inches Maximum
<b>Shear Strength:</b>	370 Single Pounds Per Square Inch
<b>Special Features:</b>	W/special Pulling Head
<b>Material:</b>	Aluminum Alloy 2117 Body
<b>Material:</b>	Aluminum Alloy 2017 Stem
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Body
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Stem
<b>Surface Treatment:</b>	Anodize Overall Or Oxide Film Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR9163-4-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.