

**Description**

diameter: 1/8", grip range: 0.313" - 0.375", universal head, self plugging, aluminum sleeve, aluminum stem, serrated

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | CR9163406           |
| Minimum Qty (MOQ):      | 100                 |
| NSN:                    | 5320-00-582-3495    |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE  
AVAILABLE

## P/N CR9163-4-06 Specifications

|                                                       |                                                                                                          |
|-------------------------------------------------------|----------------------------------------------------------------------------------------------------------|
| <b>Fastener Length:</b>                               | 0.482 Inches Maximum                                                                                     |
| <b>Head Style:</b>                                    | Universal                                                                                                |
| <b>Head Height:</b>                                   | 0.054 Inches Minimum And 0.064 Inches Maximum                                                            |
| <b>Shank Diameter:</b>                                | 0.124 Inches Minimum And 0.128 Inches Maximum                                                            |
| <b>Shank Style:</b>                                   | Self-plugging                                                                                            |
| <b>Head Major Diameter:</b>                           | 0.238 Inches Minimum And 0.262 Inches Maximum                                                            |
| <b>Expansion Device:</b>                              | Serrated Stem-type W                                                                                     |
| <b>Grip Length:</b>                                   | 0.313 Inches Minimum And 0.375 Inches Maximum                                                            |
| <b>Shear Strength:</b>                                | 370 Single Pounds Per Square Inch                                                                        |
| <b>Special Features:</b>                              | W/special Pulling Head                                                                                   |
| <b>Material:</b>                                      | Aluminum Alloy 2117 Body                                                                                 |
| <b>Material:</b>                                      | Aluminum Alloy 2017 Stem                                                                                 |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Body                                                          |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Stem                                                          |
| <b>Surface Treatment:</b>                             | Anodize Overall Or Oxide Film Overall                                                                    |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR9163-4-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.