

Description

diameter: 1/8", grip range: 0.376" - 0.437", universal head - self plugging - 2117 aluminum sleeve - 2017 aluminum stem - serrated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | CR9163407 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-00-816-7022 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N CR9163-4-07 Specifications

| | |
|--|--|
| Fastener Length: | 1.353 Inches Nominal |
| Head Style: | Brazier |
| Head Height: | 0.054 Inches Nominal |
| Shank Diameter: | 0.125 Inches Nominal |
| Shank Style: | Self-plugging |
| Head Major Diameter: | 0.250 Inches Nominal |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.375 Inches Minimum And 0.545 Inches Maximum |
| Material: | Aluminum Alloy 2117 Overall |
| Material Document And Classification: | Mil-w-7986 Mil Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR9163-4-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.