

P/N CR9163-4-07

Description

diameter: 1/8", grip range: 0.376" - 0.437", universal head - self plugging - 2117 aluminum sleeve - 2017 aluminum stem - serrated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CR9163407
Minimum Qty (MOQ):	100
NSN:	5320-00-816-7022
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



^{*} See page 2 for technical characteristics

P/N CR9163-4-07 Specifications

Fastener Length:	1.353 Inches Nominal
Head Style:	Brazier
Head Height:	0.054 Inches Nominal
Shank Diameter:	0.125 Inches Nominal
Shank Style:	Self-plugging
Head Major Diameter:	0.250 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.375 Inches Minimum And 0.545 Inches Maximum
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Mil-w-7986 Mil Spec Single Material Response Overall
Surface Treatment:	Anodize Overall

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/CR9163-4-07 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.