

## Description

diameter: 5/32", grip range: 0.025" - 0.062", universal head - self plugging - 2117 aluminum sleeve - 2017 aluminum stem - serrated"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	CR9163501
Minimum Qty (MOQ):	100
NSN:	5320-00-616-4352
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N CR9163-5-01 Specifications

<b>Fastener Length:</b>	0.192 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.067 Inches Minimum And 0.077 Inches Maximum
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.159 Inches Maximum
<b>Shank Style:</b>	Self-plugging
<b>Head Major Diameter:</b>	0.296 Inches Minimum And 0.328 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>End Item Identification:</b>	W/s: Aircraft, C-2a (reprocured); Aircraft, Hercules C-130; Aircraft, Starlifter C-141; Aircraft, Galaxy C-5; Aircraft, T-38; Aircraft, Phantom F-4; Helicopter, Hh-53h Pave Low; Aircraft, Stratofortress B-52; Aircraft, T-37; Aircraft, Stratolifter C-135
<b>Grip Length:</b>	0.062 Inches Maximum
<b>Special Features:</b>	W/special Pulling Head
<b>Material:</b>	Aluminum Alloy 2117 Body
<b>Material:</b>	Aluminum Alloy 2017 Stem
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Body
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Stem
<b>Surface Treatment:</b>	Anodize Overall Or Oxide Film Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR9163-5-01> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.