

Description

diameter: 5/32", grip range: 0.025" - 0.062", universal head - self plugging - 2117 aluminum sleeve - 2017 aluminum stem - serrated"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CR9163501
Minimum Qty (MOQ):	100
NSN:	5320-00-616-4352
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N CR9163-5-01 Specifications

Fastener Length:	0.192 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Self-plugging
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	W/s: Aircraft, C-2a (reprocured); Aircraft, Hercules C-130; Aircraft, Starlifter C-141; Aircraft, Galaxy C-5; Aircraft, T-38; Aircraft, Phantom F-4; Helicopter, Hh-53h Pave Low; Aircraft, Stratofortress B-52; Aircraft, T-37; Aircraft, Stratolifter C-135
Grip Length:	0.062 Inches Maximum
Special Features:	W/special Pulling Head
Material:	Aluminum Alloy 2117 Body
Material:	Aluminum Alloy 2017 Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Body
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Stem
Surface Treatment:	Anodize Overall Or Oxide Film Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR9163-5-01> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.