

Description

diameter: 5/32", grip range: 0.126" - 0.187", universal head, self plugging, 2117 aluminum sleeve, 2017 aluminum stem, serrated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR9163-5-3](#) [MS20600AD5W3](#)

| | |
|--------------------|------------------|
| SKU / Model: | CR9163503 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-019-1533 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N CR9163-5-03 Specifications

| | |
|---|---|
| Fastener Length: | 0.307 Inches Nominal |
| Head Style: | Universal |
| Head Height: | 0.067 Inches Nominal |
| Shank Diameter: | 0.156 Inches Nominal |
| Shank Style: | Self-plugging |
| Head Major Diameter: | 0.312 Inches Nominal |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.126 Inches Minimum And 0.187 Inches Maximum |
| Material: | Aluminum Alloy 2117 Overall Or Aluminum Alloy 2017 Overall |
| Material Document And Classification: | Aluminum Assn Of America Mfr Ref Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | 11815 Mfr Ref Single Treatment Response Overall |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR9163-5-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.