

**Description**

diameter: 5/32", grip range: 0.126" - 0.187", universal head, self plugging, 2117 aluminum sleeve, 2017 aluminum stem, serrated

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[CR9163-5-3](#) [MS20600AD5W3](#)

SKU / Model:	CR9163503
Minimum Qty (MOQ):	100
NSN:	5320-01-019-1533
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N CR9163-5-03 Specifications

<b>Fastener Length:</b>	0.307 Inches Nominal
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.067 Inches Nominal
<b>Shank Diameter:</b>	0.156 Inches Nominal
<b>Shank Style:</b>	Self-plugging
<b>Head Major Diameter:</b>	0.312 Inches Nominal
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.126 Inches Minimum And 0.187 Inches Maximum
<b>Material:</b>	Aluminum Alloy 2117 Overall Or Aluminum Alloy 2017 Overall
<b>Material Document And Classification:</b>	Aluminum Assn Of America Mfr Ref Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	11815 Mfr Ref Single Treatment Response Overall

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR9163-5-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.