

## P/N CR9179-4-02

## **Description**

Diameter: 1/8", grip range: 0.063" - 0.125", universal head, oversized diameter, self plugging, aluminum sleeve, aluminum stem, serrated

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

CR9179-4-2

SKU / Model: CR9179402

Minimum Qty (MOQ): 100

NSN: 5320-01-089-1608

ECCN: EAR99









<sup>\*</sup> See page 2 for technical characteristics

# P/N CR9179-4-02 Specifications

Fastener Length:	0.212 Inches Minimum And 0.232 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Countersink Height:	0.133 Inches Minimum And 0.137 Inches Maximum
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum

## **How to Order**

Order this blind rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/CR9179-4-02">https://military-fasteners.com/rivets/blind+rivets/CR9179-4-02</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/CR9179-4-02">https://military-fasteners.com/rivets/blind+rivets/CR9179-4-02</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/CR9179-4-02">https://military-fasteners.com/rivets/blind+rivets/CR9179-4-02</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/CR9179-4-02">https://military-fasteners.com/rivets/blind+rivets/CR9179-4-02</a> and selecting the quantity you want then