

Description

diameter: 1/8", grip range: 0.188" - 0.250", universal head - oversized diameter - self plugging - 2117 aluminum sleeve - 2017 aluminum stem - serrated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | CR9179404 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-00-582-3517 |
| National Motor Freight: | 013630, Alum Rivets |



P/N CR9179-4-04 Specifications

| | |
|---|---|
| Fastener Length: | 0.357 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.054 Inches Minimum And 0.064 Inches Maximum |
| Shank Diameter: | 0.133 Inches Minimum And 0.137 Inches Maximum |
| Shank Style: | Self-plugging High Clinch Shank |
| Head Major Diameter: | 0.238 Inches Minimum And 0.262 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.188 Inches Minimum And 0.250 Inches Maximum |
| Special Features: | Sleeve Dyed Blue; W/special Pulling Head |
| Material: | Aluminum Alloy 2117 Stem |
| Material: | Aluminum Alloy 2017 Sleeve |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Sleeve |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Stem |
| Surface Treatment: | Oxide Film Overall |
| Surface Treatment Document And Classification: | Mil-c-5541 Mil Spec Single Treatment Response Overall |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR9179-4-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.