

Description

flush flat head, titanium alloy

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CSR902B4-5](#)

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | CSR902B45 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-00-162-7248 |
| ECCN: | EAR99 |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |



* See page 2 for technical characteristics

P/N CSR902B-4-5 Specifications

| | |
|--|--|
| Fastener Length: | 0.302 Inches Minimum And 0.322 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.124 Inches Minimum And 0.128 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.207 Inches Minimum And 0.229 Inches Maximum |
| Shear Strength: | 50000 Single Pounds Per Square Inch |
| Countersink Angle: | 98.5 Degrees Minimum And 101.5 Degrees Maximum |
| Material: | Titanium Alloy Overall |
| Material Document And Classification: | -172,fscm 11815 Mfr Ref Single Material Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/CSR902B-4-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.