

Description

Fastener Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	CSR903B56
Minimum Qty (MOQ):	5
NSN:	5320-00-170-3544
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CSR903B-5-6 Specifications

Fastener Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Shear Strength:	50000 Single Pounds Per Square Inch
Heat Treatment:	Annealed Overall
Material:	Titanium Alloy Overall
Material Document And Classification:	-172,fscm 11815 Mfr Ref Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/CSR903B-5-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.