

Description

CSR903B4-3 Solid Rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS20470T4-3](#)

SKU / Model:	CSR903B43
Minimum Qty (MOQ):	50
NSN:	5320-00-170-3039
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



* See page 2 for technical characteristics

P/N CSR903B4-3 Specifications

Fastener Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Shear Strength:	50000 Single Pounds Per Square Inch
Heat Treatment:	Annealed Overall
Material:	Titanium Alloy Overall
Material Document And Classification:	-172,fscm 11815 Mfr Ref Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/CSR903B4-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.