

Description

Fastener Length: 1/4", Hole Diameter: 1/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|--------------------|------------------|
| SKU / Model: | CSR9043B5F5 |
| Minimum Qty (MOQ): | 20 EA |
| NSN: | 5320-01-515-7328 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |



NO IMAGE
AVAILABLE

P/N CSR9043B-5F-5 Specifications

| | |
|--|--|
| Fastener Length: | 0.191 Inches Minimum And 0.201 Inches Maximum |
| Head Style: | Cooper's (included Angle - 135 Deg And Over) |
| Hole Diameter: | 0.091 Inches Minimum And 0.096 Inches Maximum |
| Shank Diameter: | 0.156 Inches Minimum And 0.159 Inches Maximum |
| Shank Style: | Tubular |
| Hole Depth: | 0.105 Inches Nominal |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Heat Treatment: | Annealed Overall |
| Material: | Titanium Alloy Overall |
| Material Document And Classification: | Ams 4982 Assn Std Single Material Response Overall |
| Surface Treatment: | Phosphate Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/CSR9043B-5F-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.