

**Description**

Fastener Length: 1/4", Hole Diameter: 1/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	CSR9043B5F6
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-515-7329
Schedule B:	8108.90.3060
ECCN:	EAR99

A circular placeholder with a thin grey border containing the text "NO IMAGE AVAILABLE" in a sans-serif font.

NO IMAGE  
AVAILABLE

## P/N CSR9043B-5F-6 Specifications

<b>Fastener Length:</b>	0.222 Inches Minimum And 0.232 Inches Maximum
<b>Head Style:</b>	Cooper's (included Angle - 135 Deg And Over)
<b>Hole Diameter:</b>	0.091 Inches Minimum And 0.096 Inches Maximum
<b>Shank Diameter:</b>	0.156 Inches Minimum And 0.159 Inches Maximum
<b>Shank Style:</b>	Tubular
<b>Hole Depth:</b>	0.105 Inches Nominal
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Heat Treatment:</b>	Annealed Overall
<b>Material:</b>	Titanium Alloy Overall
<b>Material Document And Classification:</b>	Ams 4982 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Phosphate Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/CSR9043B-5F-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.