

Description

Fastener Length: 1/4", Hole Diameter: 1/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CSR9043B5F6
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-515-7329
Schedule B:	8108.90.3060
ECCN:	EAR99



* See page 2 for technical characteristics

P/N CSR9043B-5F-6 Specifications

Fastener Length:	0.222 Inches Minimum And 0.232 Inches Maximum
Head Style:	Cooper's (included Angle - 135 Deg And Over)
Hole Diameter:	0.091 Inches Minimum And 0.096 Inches Maximum
Shank Diameter:	0.156 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Tubular
Hole Depth:	0.105 Inches Nominal
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Heat Treatment:	Annealed Overall
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams 4982 Assn Std Single Material Response Overall
Surface Treatment:	Phosphate Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/CSR9043B-5F-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.