

Description

high tensile 180,000 psi

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	DHN358
Minimum Qty (MOQ):	1
NSN:	5310-00-297-3721
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N DHN35-8 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque With Nonmetallic Insert
Washer Outside Diameter:	0.865 Inches Minimum And 0.875 Inches Maximum
Overall Height:	0.563 Inches Nominal
Nut Style:	Double Hexagon
Washer Thickness:	0.118 Inches Nominal
Width Across Flats:	0.612 Inches Minimum And 0.628 Inches Maximum
Temp Rating:	250.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	20
Nominal Thread Size:	0.500 Inches
Material:	Plastic Polyamide Locking Insert
Material:	Steel Comp 4130 Nut Or Steel Comp 4340 Nut Or Steel Comp 3140 Nut Or Steel Comp 8740 Nut
Material Document And Classification:	Aisi Assn Std All Material Responses Nut
Surface Treatment:	Cadmium Overall Except Insert
Surface Treatment Document And Classification:	Qq-p-416,ty 1,c1 3 Fed Spec Single Treatment Response Overall Except Insert

How to Order

Order this self-locking extended washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/DHN35-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.