

**Description**

Fastener Length: 33/64", Thread: 6-32, Thread Length: 1/4

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	DP79506B8
Minimum Qty (MOQ):	1
NSN:	5305-01-362-6170
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N DP7950-6-B-8 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.250 Inches Nominal
<b>Fastener Length:</b>	0.480 Inches Minimum And 0.520 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.270 Inches Nominal
<b>Head Height:</b>	0.095 Inches Minimum And 0.145 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Material Accommodated Thickness:</b>	0.049 Inches Minimum And 0.075 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Material:</b>	Aluminum Alloy 7075 Stand-offsteel Fastener Or Steel Comp 302 Fastener
<b>Material Document And Classification:</b>	Qq-a-225/9 Fed Spec 1st Material Response Stand-off Or Ams 4122 Assn Std 2nd Material Response Stand-offastm-a-581 Assn Std 1st Material Response Fastener Or Ams 5636 Assn Std 2nd Material Response Fastener
<b>Surface Treatment:</b>	Chromate Stand-off Or Anodize Stand-offpassivate Fastener
<b>Surface Treatment Document And Classification:</b>	Bmil-c-5541 Mil Spec 1st Treatment Response Stand-off Or Mil-a-8625 Mil Spec 2nd Treatment Response Stand-offqq-p-35 Fed Spec 1st Treatment Response Fastener
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/DP7950-6-B-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.