

Description

Fastener Length: 33/64", Thread: 6-32, Thread Length: 1/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	DP79506B8
Minimum Qty (MOQ):	1
NSN:	5305-01-362-6170
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N DP7950-6-B-8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.250 Inches Nominal
Fastener Length:	0.480 Inches Minimum And 0.520 Inches Maximum
Head Style:	Pan
Head Diameter:	0.270 Inches Nominal
Head Height:	0.095 Inches Minimum And 0.145 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Material Accommodated Thickness:	0.049 Inches Minimum And 0.075 Inches Maximum
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Material:	Aluminum Alloy 7075 Stand-offsteel Fastener Or Steel Comp 302 Fastener
Material Document And Classification:	Qq-a-225/9 Fed Spec 1st Material Response Stand-off Or Ams 4122 Assn Std 2nd Material Response Stand-offastm-a-581 Assn Std 1st Material Response Fastener Or Ams 5636 Assn Std 2nd Material Response Fastener
Surface Treatment:	Chromate Stand-off Or Anodize Stand-offpassivate Fastener
Surface Treatment Document And Classification:	Bmil-c-5541 Mil Spec 1st Treatment Response Stand-off Or Mil-a-8625 Mil Spec 2nd Treatment Response Stand-offqq-p-35 Fed Spec 1st Treatment Response Fastener
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/DP7950-6-B-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.