

## **P/N EB048**

### **Description**

Thread: 1/4-28, high tensile 180,000 psi

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: EB048

Minimum Qty (MOQ): 5

NSN: 5310-00-488-9137

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# **P/N EB048 Specifications**

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque With Nonmetallic Insert
Washer Outside Diameter:	0.521 Inches Minimum And 0.531 Inches Maximum
Overall Height:	0.334 Inches Nominal
Nut Style:	Double Hexagon
Washer Thickness:	0.090 Inches Nominal
Width Across Flats:	0.362 Inches Minimum And 0.377 Inches Maximum
Temp Rating:	250.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Material:	Steel Comp 4130 Overall Or Steel Comp 4340 Overall Or Steel Comp 3140 Overall Or Steel Comp 8740 Overall
Material Document And	Aisi4130 Assn Std Single Material Response Overall Or Aisi4340 Assn Std Single Material Response Overall Or Aisi3140 Assn Std Single
Classification:	Material Response Overall Or Sae8740 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall Except Insert And Chromate Overall Except Insert
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall

## **How to Order**

Order this self-locking extended washer nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+extended+washer+nuts/EB048">https://military-fasteners.com/nuts/self\_locking+extended+washer+nuts/EB048</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.