

Description

high tensile 180,000 psi

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | EB070 |
| Minimum Qty (MOQ): | 2 |
| NSN: | 5310-00-297-3722 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N EB070 Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque With Nonmetallic Insert |
| Washer Outside Diameter: | 0.771 Inches Minimum And 0.781 Inches Maximum |
| Overall Height: | 0.516 Inches Nominal |
| Nut Style: | Double Hexagon |
| Washer Thickness: | 0.107 Inches Nominal |
| Width Across Flats: | 0.550 Inches Minimum And 0.565 Inches Maximum |
| Temp Rating: | 250.0 Deg Fahrenheit Nominal |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 20 |
| Nominal Thread Size: | 0.438 Inches |
| Material: | Plastic Polyamide Locking Insert |
| Material: | Steel Comp 4130 Nut Or Steel Comp 4340 Nut Or Steel Comp 3140 Nut Or Steel Comp 8740 Nut |
| Material Document And Classification: | Aisi Assn Std All Material Responses Nut |
| Surface Treatment: | Cadmium Overall Except Insert |
| Surface Treatment Document And Classification: | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Overall Except Insert |

How to Order

Order this self-locking extended washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/EB070 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.